




Mini industrial coupling in plastics POM and PVDF with the world's most popular profile in this nominal diameter. Above average flow performance for liquid and gaseous media. Coupling system with single-hand operation. This new type of plastic locking system with handy sleeve considerably expands the applications of this series. Two sleeve forms - tapered and cylindrical, where the tapered sleeve form facilitates handling with gloves. The color coding of the coupling and plug offers a guarantee for avoiding mix-ups between media when coupling.

- Available valve types:

- Single Shut-off
- Double Shut-off



RectuPOM

Working Pressure*:

up to 10 bar (POM, at 20°C)

Material:

- Coupling: POM black
- Plug: POM black
- Seals: NBR

Working Temperature:


-20°C up to +80°C (POM)

Flow Rate Air:

- Single Shut-Off: 550 l/min.
 - Double Shut-Off: 310 l/min.
- inlet pressure 6 bar, pressure drop 0.5 bar

Flow Rate Water:

- Single Shut-Off: 7 l/min.
 - Double Shut-Off: 2.7 l/min.
- pressure drop 0.5 bar



RectuChem

Working Pressure*:

up to 8 bar (PVDF, at 20°C)

Material:

- Coupling: PVDF white
- Plug: PVDF white
- Seals: FKM

Working Temperature:

-20°C up to +120°C (PVDF)



Flow Rate Air:

- Single Shut-Off: 550 l/min.
 - Double Shut-Off: 310 l/min.
- inlet pressure 6 bar, pressure drop 0.5 bar

Flow Rate Water:

- Single Shut-Off: 7 l/min.
 - Double Shut-Off: 2.7 l/min.
- pressure drop 0.5 bar

* maximum static working pressure with design factor 4 to 1.





Single Shut-Off / Double Shut-off







	Connection A	HEX	HEX1	L	L1	L2	D	B	G	Color Sleeve	Part Number POM	Part Number CHEM
 21KBAW Coupler with valve, Male Thread with tapered sleeve	G1/8	17		50	7		25.5			Standard	21KBAW10DPX	21KBAW10FVX
	G1/4	17		50	7		25.5			Standard	21KBAW13DPX	21KBAW13FVX
	G1/8	17		50	7		21			Blue	21KBAW10DPXGB	21KBAW10FVXGB
	G1/8	17		50	7		21			Red	21KBAW10DPXGR	21KBAW10FVXGR
 21KBAW Coupler with valve, Male Thread with cylindrical sleeve	G1/8	17		50	7		21			Standard	21KBAW10DPXG	21KBAW10FVXG
	G1/4	17		50	7		21			Blue	21KBAW13DPXGB	21KBAW13FVXGB
	G1/4	17		50	7		21			Red	21KBAW13DPXGR	21KBAW13FVXGR
	G1/4	17		50	7		21			Standard	21KBAW13DPXG	21KBAW13FVXG

Series 21 - Thermoplastic





Single Shut-Off / Double Shut-off








	Connection A	HEX	HEX1	L	L1	L2	D	B	G	Color Sleeve	Part Number POM	Part Number CHEM
 21KBIW Coupler with valve, Male Thread with tapered sleeve	G1/8	17		53	8		25.5			Standard	21KBIW10DPX	21KBIW10FVX
	G1/4	17		39	9		25.5			Standard	21KBIW13DPX	21KBIW13FVX
	G1/8	17		53	8		21			Blue	21KBIW10DPXGB	21KBIW10FVXGB
 21KBIW Coupler with valve, Female Thread with cylindrical sleeve	G1/8	17		53	8		21			Standard	21KBIW10DPXG	21KBIW10FVXG
	G1/4	17		39	9		21			Blue	21KBIW13DPXGB	21KBIW13FVXGB
	G1/4	17		39	9		21			Red	21KBIW13DPXGR	21KBIW13FVXGR
	G1/4	17		39	9		21			Standard	21KBIW13DPXG	21KBIW13FVXG
	4 x 6	17	27	56	7	20.5	28	7	M25x1	Standard	21KBKE06DPX	21KBKE06FVX
	6 x 8	17	27	56	7	20.5	28	7	M25x1	Standard	21KBKE08DPX	21KBKE08FVX
 21KBK0 Coupler with valve, with Plastic Hose Connection with tapered sleeve	4 x 6	17		56	6	7	25.5		M10x1	Standard	21KBK006DPX	21KBK006FVX
	6 x 8	17		56	6	7	25.5		M12x1	Standard	21KBK008DPX	21KBK008FVX
	4 x 6	17		56	6	7	21			Blue	21KBK006DPXGB	21KBK006FVXGB
 21KBK0 Coupler with valve, with Plastic Hose Connection with cylindrical sleeve	4 x 6	17		56	6	7	21			Red	21KBK006DPXGR	21KBK006FVXGR
	4 x 6	17		56	6	7	21			Standard	21KBK006DPXG	21KBK006FVXG
	6 x 8	17		56	6	7	21			Blue	21KBK008DPXGB	21KBK008FVXGB
	6 x 8	17		56	6	7	21			Red	21KBK008DPXGR	21KBK008FVXGR
	6 x 8	17		56	6	7	21			Standard	21KBK008DPXG	21KBK008FVXR
	6 x 8	17		56	6	7	21			Standard	21KBK008DPXG	21KBK008FVXR

Series 21 - Thermoplastic





Single Shut-Off / Double Shut-off





	Connection A	HEX	HEX1	L	L1	L2	D	B	G	Color Sleeve	Part Number POM	Part Number CHEM
 21KBKS Coupler with valve, Panel Mount with Plastic Hose Connection with tapered sleeve	4 x 6	17	14	68	7	18	25.5	4	M10x1	Standard	21KBKS06DPX	21KBKS06FVX
	6 x 8	17	17	68	7	18	25.5	4	M12x1	Standard	21KBKS08DPX	21KBKS08FVX
	4 x 6	17	14	68	7	18	21	4	M10x1	Blue	21KBKS06DPXGB	21KBKS06FVXGB
 21KBKS Coupler with valve, Panel Mount with Plastic Hose Connection with cylindrical sleeve	4 x 6	17	14	68	7	18	21	4	M10x1	Red	21KBKS06DPXGR	21KBKS06FVXGR
	4 x 6	17	14	68	7	18	21	4	M10x1	Standard	21KBKS06DPXG	21KBKS06FVXG
	6 x 8	17	17	68	7	18	21	4	M12x1	Blue	21KBKS08DPXGB	21KBKS08FVXGB
	6 x 8	17	17	68	7	18	21	4	M12x1	Red	21KBKS08DPXGR	21KBKS08FVXGR
	6 x 8	17	17	68	7	18	21	4	M12x1	Standard	21KBKS08DPXG	21KBKS08FVXG
 21KBTE Coupler with valve, Panel Mount for Hose Barb for Front Panel Installation	4	17	27	60	17	20.5	28	7	M25x1	Standard	21KBTE04DPX	21KBTE04FVX
	6	17	27	60	17	20.5	28	7	M25x1	Standard	21KBTE06DPX	21KBTE06FVX
 21KBTF Coupler with valve, Hose Barb with tapered sleeve	4	17		60	17		25.5			Standard	21KBTF04DPX	21KBTF04FVX
	6	17		60	17		25.5			Standard	21KBTF06DPX	21KBTF06FVX
	4	17		60	17		21			Blue	21KBTF04DPXGB	21KBTF04FVXGB
	4	17		60	17		21			Red	21KBTF04DPXGR	21KBTF04FVXGR
	4	17		60	17		21			Standard	21KBTF04DPXG	21KBTF04FVXG
	6	17		60	17		21			Blue	21KBTF06DPXGB	21KBTF06FVXGB
	6	17		60	17		21			Red	21KBTF06DPXGR	21KBTF06FVXGR
	6	17		60	17		21			Standard	21KBTF06DPXG	21KBTF06FVXG
 21KBTF Coupler with valve, Hose Barb with cylindrical sleeve	4	17		60	17		21			Standard	21KBTF04DPXG	21KBTF04FVXG
	6	17		60	17		21			Blue	21KBTF06DPXGB	21KBTF06FVXGB
	6	17		60	17		21			Red	21KBTF06DPXGR	21KBTF06FVXGR
	6	17		60	17		21			Standard	21KBTF06DPXG	21KBTF06FVXG


Series 21 - Thermoplastic



Single Shut-Off / Double Shut-off



	Connection A	HEX	HEX1	L	L1	L2	D	B	G	Color Sleeve	Part Number POM	Part Number CHEM
 21KBT Coupler with valve, Panel Mount with Hose Barb with tapered sleeve	4	17	14	74	17	14	25.5	4	M10x1	Standard	21KBT04DPX	21KBT04FVX
	6	17	14	74	17	14	25.5	4	M10x1	Standard	21KBT06DPX	21KBT06FVX
 21KBT Coupler with valve, Panel Mount with Hose Barb with cylindrical sleeve	4	17	14	74	17	14	21	4	M10x1	Blue	21KBT04DPXGB	21KBT04FVXGB
	4	17	14	74	17	14	21	4	M10x1	Red	21KBT04DPXGR	21KBT04FVXGR
	4	17	14	74	17	14	21	4	M10x1	Standard	21KBT04DPXG	21KBT04FVXG
	6	17	17	74	17	14	21	4	M12x1	Blue	21KBT06DPXGB	21KBT06FVXGB
	6	17	17	74	17	14	21	4	M12x1	Red	21KBT06DPXGR	21KBT06FVXGR
	6	17	17	74	17	14	21	4	M12x1	Standard	21KBT06DPXG	21KBT06FVXG





Single Shut-Off




	Connection A	HEX	HEX1	L	L1	L2	D	B	G	Color Sleeve	Part Number POM	Part Number CHEM
 21SFAW Plug without valve, Male Thread	G1/4	17		28	9					Standard	21SFAW13DXX	21SFAW13FXX
	G1/4	17		25	9					Blue	21SFIW13DXXB	21SFIW13FXXB
 21SFIW Plug without valve, Female Thread	G1/4	17		25	9					Red	21SFIW13DXXR	21SFIW13FXXR
	G1/4	17		25	9					Standard	21SFIW13DXX	21SFIW13FXX
	4			32	17					Standard	21SFTF04DXX	21SFTF04FXX
 21SFTF Plug without valve, Hose Barb	6			32	17					Standard	21SFTF06DXX	21SFTF06FXX

Series 21 - Thermoplastic




Single Shut-Off / Double Shut-off




21SBAW

Plug with valve, Male Thread



21SBIW

Plug with valve, Female Thread




21SBKO


Plug with valve, with Plastic Hose Connection

Connection A	HEX	HEX1	L	L1	L2	D	B	G	Color Sleeve	Part Number POM	Part Number CHEM
G1/8	17		36	7					Blue	21SBAW10DPXB	21SBAW10FVXB
G1/8	17		36	7					Red	21SBAW10DPXR	21SBAW10FVXR
G1/8	17		36	7					Standard	21SBAW10DPX	21SBAW10FVX
G1/4	17		38	7					Blue	21SBAW13DPXB	21SBAW13FVXB
G1/4	17		38	7					Red	21SBAW13DPXR	21SBAW13FVXR
G1/4	17		38	7					Standard	21SBAW13DPX	21SBAW13FVX
G1/8	17		39	8					Blue	21SBIW10DPXB	21SBIW10FVXB
G1/8	17		39	8					Red	21SBIW10DPXR	21SBIW10FVXR
G1/8	17		39	8					Standard	21SBIW10DPX	21SBIW10FVX
G1/4	17		42	10					Blue	21SBIW13DPXB	21SBIW13FVXB
G1/4	17		42	10					Red	21SBIW13DPXR	21SBIW13FVXR
G1/4	17		42	10					Standard	21SBIW13DPX	21SBIW13FVX
4 x 6	17		42	7	6				Blue	21SBK006DPXB	21SBK006FVXB
4 x 6	17		42	7	6				Red	21SBK006DPXR	21SBK006FVXR
4 x 6	17		42	7	6				Standard	21SBK006DPX	21SBK006FVX
6 x 8	17		42	7	6				Blue	21SBK008DPXB	21SBK008FVXB
6 x 8	17		42	7	6				Red	21SBK008DPXR	21SBK008FVXR
6 x 8	17		42	7	6				Standard	21SBK008DPX	21SBK008FVX

Series 21 - Thermoplastic




Double Shut-Off




21SBKS

Plug with valve, Panel Mount with Plastic Hose Connection



21SBTF

Plug with valve, Hose Barb




21SBTS

Plug with valve, Panel Mount with Hose Barb

	Connection A	HEX	HEX1	L	L1	L2	D	B	G	Color Sleeve	Part Number POM	Part Number CHEM
	4 x 6	17	14	54	7	18		4	M10x1	Blue	21SBKS06DPXB	21SBKS06FVXB
	4 x 6	17	14	54	7	18		4	M10x1	Red	21SBKS06DPXR	21SBKS06FVXR
	4 x 6	17	14	54	7	18		4	M10x1	Standard	21SBKS06DPX	21SBKS06FVX
	6 x 8	17	17	54	7	18		4	M12x1	Blue	21SBKS08DPXB	21SBKS08FVXB
	6 x 8	17	17	54	7	18		4	M12x1	Red	21SBKS08DPXR	21SBKS08FVXR
	6 x 8	17	17	54	7	18		4	M12x1	Standard	21SBKS08DPX	21SBKS08FVX
	4	17		46	17					Standard	21SBTF04DPX	21SBTF04FVX
	4	17		46	17					Blue	21SBTF04DPXB	21SBTF04FVXB
	4	17		46	17					Red	21SBTF04DPXR	21SBTF04FVXR
	6	17		46	17					Standard	21SBTF06DPX	21SBTF06FVX
	6	17		46	17					Blue	21SBTF06DPXB	21SBTF06FVXB
	6	17		46	17					Red	21SBTF06DPXR	21SBTF06FVXR
	4	17	14	60	7	14		4	M10x1	Blue	21SBTS04DPXB	21SBTS04FVXB
	4	17	14	60	7	14		4	M10x1	Red	21SBTS04DPXR	21SBTS04FVXR
	4	17	14	60	7	14		4	M10x1	Standard	21SBTS04DPX	21SBTS04FVX
	6	17	17	60	7	14		4	M12x1	Blue	21SBTS06DPXB	21SBTS06FVXB
	6	17	17	60	7	14		4	M12x1	Red	21SBTS06DPXR	21SBTS06FVXR
	6	17	17	60	7	14		4	M12x1	Standard	21SBTS06DPX	21SBTS06FVX




Coupling series made of POM and PVDF has been developed for use in the medical, chemical, food handling, pharmaceutical and laboratory technology industries. The system is also available in a solid plastic design (RectuChem+). Here the metal springs are replaced by springs made of PEEK, an extremely resistant synthetic material. Coupling system with single-hand operation. The color coding of the coupling and plug offers a guarantee for avoiding mix-ups between media when coupling. The coupling is also available with no valve for a straight-through system.



- Available valve types:

- Single Shut-off
- Double Shut-off



RectuPOM

Working Pressure*:

up to 10 bar (POM, at 20°C)

Material:

- Coupling: POM black
- Plug: POM black
- Seals: NBR

Working Temperature:


-20°C up to +80°C (POM)

Flow Rate Air:

- Single Shut-Off: 1.100 l/min.
 - Double Shut-Off: 770 l/min.
- inlet pressure 6 bar, pressure drop 0.5 bar

Flow Rate Water:

- Single Shut-Off: 17 l/min.
 - Double Shut-Off: 12 l/min.
- pressure drop 0.5 bar



RectuChem

Working Pressure*:

up to 8 bar (PVDF, with metal springs)

Material:

- Coupling: PVDF white
- Plug: PVDF white
- Seals: FKM

Working Temperature:


-20°C up to +120°C (PVDF)

Flow Rate Air:

- Single Shut-Off: 1.100 l/min.
 - Double Shut-Off: 770 l/min.
- inlet pressure 6 bar, pressure drop 0.5 bar

Flow Rate Water:

- Single Shut-Off: 17 l/min.
 - Double Shut-Off: 12 l/min.
- pressure drop 0.5 bar



RectuChem+

Working Pressure*:

1-8 bar (PVDF, with PEEK-spring)

Material:

- Coupling: PVDF white, PEEK-spring
- Plug: PVDF white, PEEK-spring
- Seals: FKM

Working Temperature:

-20°C up to +120°C (PVDF)



Flow Rate Air:

- Double Shut-Off: 770 l/min.
- inlet pressure 6 bar, pressure drop 0.5 bar


Flow Rate Water:

- Double Shut-Off: 12 l/min.
- pressure drop 0.5 bar

* maximum static working pressure with design factor 4 to 1.





Single Shut-Off / Double Shut-off





Connection A	HEX	L	L1	D	Color Sleeve	Part Number POM	Part Number CHEM	Part Number CHEM+
G1/4	21	70.5	9	26	Standard	48KBAW13DPX	48KBAW13FVX	48KBAW13FVP
G1/4	21	70.5	9	26	Red	48KBAW13DPXR	48KBAW13FVXR	48KBAW13FVPR
G1/4	21	70.5	9	26	Blue	48KBAW13DPXB	48KBAW13FVXB	48KBAW13FVPB
G3/8	21	67	9	26	Standard	48KBAW17DPX	48KBAW17FVX	48KBAW17FVP
G3/8	21	67	9	26	Red	48KBAW17DPXR	48KBAW17FVXR	48KBAW17FVPR
G3/8	21	67	9	26	Blue	48KBAW17DPXB	48KBAW17FVXB	48KBAW17FVPB
G1/2	21	73.5	12	26	Standard	48KBAW21DPX	48KBAW21FVX	48KBAW21FVP
G1/2	21	73.5	12	26	Red	48KBAW21DPXR	48KBAW21FVXR	48KBAW21FVPR
G1/2	21	73.5	12	26	Blue	48KBAW21DPXB	48KBAW21FVXB	48KBAW21FVPB

Series 48 - Thermoplastic




Single Shut-Off / Double Shut-off






Connection A	HEX	L	L1	D	Color Sleeve	Part Number POM	Part Number CHEM	Part Number CHEM+
G1/4	21	63.5	10	26	Standard	48KBIW13DPX	48KBIW13FVX	48KBIW13FVP
G1/4	21	63.5	10	26	Red	48KBIW13DPXR	48KBIW13FVXR	48KBIW13FVPR
G1/4	21	63.5	10	26	Blue	48KBIW13DPXB	48KBIW13FVXB	48KBIW13FVPB
G3/8	21	63.5	13	26	Standard	48KBIW17DPX	48KBIW17FVX	48KBIW17FVP
G3/8	21	63.5	13	26	Red	48KBIW17DPXR	48KBIW17FVXR	48KBIW17FVPR
G3/8	21	63.5	13	26	Blue	48KBIW17DPXB	48KBIW17FVXB	48KBIW17FVPB
G1/2	21	74.5	13	26	Standard	48KBIW21DPX	48KBIW21FVX	48KBIW21FVP
G1/2	21	74.5	13	26	Red	48KBIW21DPXR	48KBIW21FVXR	48KBIW21FVPR
G1/2	21	74.5	13	26	Blue	48KBIW21DPXB	48KBIW21FVXB	48KBIW21FVPB
6	21	81	22	26	Standard	48KBTf06DPX	48KBTf06FVX	48KBTf06FVP
6	21	81	22	26	Red	48KBTf06DPXR	48KBTf06FVXR	48KBTf06FVPR
6	21	81	22	26	Blue	48KBTf06DPXB	48KBTf06FVXB	48KBTf06FVPB
9	21	81	22	26	Standard	48KBTf09DPX	48KBTf09FVX	48KBTf09FVP
9	21	81	22	26	Red	48KBTf09DPXR	48KBTf09FVXR	48KBTf09FVPR
9	21	81	22	26	Blue	48KBTf09DPXB	48KBTf09FVXB	48KBTf09FVPB
13	21	84	25	26	Standard	48KBTf13DPX	48KBTf13FVX	48KBTf13FVP
13	21	84	25	26	Red	48KBTf13DPXR	48KBTf13FVXR	48KBTf13FVPR
13	21	84	25	26	Blue	48KBTf13DPXB	48KBTf13FVXB	48KBTf13FVPB


Series 48 - Thermoplastic



Single Shut-Off




	Connection A	HEX	L	L1	D	Color Sleeve	Part Number POM	Part Number CHEM	Part Number CHEM+
 48SFAW Plug without valve, Male Thread	G3/8	21	38.5	9		Standard	48SFAW17DXX	48SFAW17FXX	
	G3/8	21	35.5	10		Standard	48SFIW17DXX	48SFIW17FXX	
 48SFIW Plug without valve, Female Thread	G3/8	21	35.5	10		Red	48SFIW17DXXR	48SFIW17FXXR	
	G3/8	21	35.5	10		Blue	48SFIW17DXXB	48SFIW17FXXB	
 48SFTF Plug without valve, Hose Barb	9		47	22	18	Standard	48SFTF09DXX	48SFTF09FXX	




Double Shut-off







	Connection A	HEX	L	L1	D	Color Sleeve	Part Number POM	Part Number CHEM	Part Number CHEM+
 48SBAW Plug with valve, Male Thread	G1/4	21	55	9		Standard	48SBAW13DPX	48SBAW13FVX	48SBAW13DPX
	G1/4	21	55	9		Red	48SBAW13DPXR	48SBAW13FVXR	48SBAW13DPX
	G1/4	21	55	9		Blue	48SBAW13DPXB	48SBAW13FVXB	48SBAW13DPX
	G3/8	21	51.5	9		Standard	48SBAW17DPX	48SBAW17FVX	48SBAW17FVP
	G3/8	21	51.5	9		Red	48SBAW17DPXR	48SBAW17FVXR	48SBAW17FVPR
	G3/8	21	51.5	9		Blue	48SBAW17DPXB	48SBAW17FVXB	48SBAW17FVPB
	G1/2	21	58	12		Standard	48SBAW21DPX	48SBAW21FVX	48SBAW21FVP
	G1/2	21	58	12		Red	48SBAW21DPXR	48SBAW21FVXR	48SBAW21FVPR
	G1/2	21	58	12		Blue	48SBAW21DPXB	48SBAW21FVXB	48SBAW21FVPB

Series 48 - Thermoplastic



Double Shut-off



	Connection A	HEX	L	L1	D	Color Sleeve	Part Number POM	Part Number CHEM	Part Number CHEM+
	G1/4	21	48	10		Standard	48SBIW13DPX	48SBIW13FVX	48SBIW13FVP
	G1/4	21	48	10		Red	48SBIW13DPXR	48SBIW13FVXR	48SBIW13FVPR
	G1/4	21	48	10		Blue	48SBIW13DPXB	48SBIW13FVXB	48SBIW13FVPB
	G3/8	21	48	10		Standard	48SBIW17DPX	48SBIW17FVX	48SBIW17FVP
	G3/8	21	48	10		Red	48SBIW17DPXR	48SBIW17FVXR	48SBIW17FVPR
	G3/8	21	48	10		Blue	48SBIW17DPXB	48SBIW17FVXB	48SBIW17FVPB
	G1/2	21	59	13		Standard	48SBIW21DPX	48SBIW21FVX	48SBIW21FVP
	G1/2	21	59	13		Red	48SBIW21DPXR	48SBIW21FVXR	48SBIW21FVPR
	G1/2	21	59	13		Blue	48SBIW21DPXB	48SBIW21FVXB	48SBIW21FVPB
	6	21	65.5	22		Standard	48SBTF06DPX	48SBTF06FVX	48SBTF06FVP
	6	21	65.5	22		Red	48SBTF06DPXR	48SBTF06FVXR	48SBTF06FVPR
	6	21	65.5	22		Blue	48SBTF06DPXB	48SBTF06FVXB	48SBTF06FVPB
	9	21	65.5	22		Standard	48SBTF09DPX	48SBTF09FVX	48SBTF09FVP
	9	21	65.5	22		Red	48SBTF09DPXR	48SBTF09FVXR	48SBTF09FVPR
	9	21	65.5	22		Blue	48SBTF09DPXB	48SBTF09FVXB	48SBTF09FVPB
	13	21	68.5	25		Standard	48SBTF13DPX	48SBTF13FVX	48SBTF13FVP
	13	21	68.5	25		Red	48SBTF13DPXR	48SBTF13FVXR	48SBTF13FVPR
	13	21	68.5	25		Blue	48SBTF13DPXB	48SBTF13FVXB	48SBTF13FVPB

Schnellkupplungen Kunststoff

PVDF, POM

Coupleurs rapides en plastique

PVDF, POM

Quick-disconnect couplings in plastic

PVDF, POM



Seite/Page/Page

Seite/Page/Page

Schnellkupplungen PVDF
Coupleur rapide PVDF
Quick couplings PVDF
Schnellkupplungen POM
Coupleur rapide POM
Quick couplings POM

Sicherheitskupplung "Kuppler"
Accouplement de sécurité "coupleur"
Safety coupling "coupler"

627-632


Serie PMC/PLC "Kuppler"
Série PMC/PLC "coupleur"
Series PMC/PLC "coupler"

644-648


Sicherheitskupplung "Stecker"
Accouplement de sécurité "embout"
Safety coupling "nipple"

632-634


Serie PMC/PLC "Stecker"
Série PMC/PLC "embout"
Series PMC/PLC "nipple"

648-650


Kupplung Plus "Kuppler"
Accouplement Plus "coupleur"
Coupling Plus "coupler"

635-637


Kupplung Plus "Stecker"
Accouplement de sécurité "embout"
Coupling Plus "nipple"

637


Serie 21 "Kuppler"
Série 21 "coupleur"
Series 21 "coupler"


638-640


Serie 21 "Stecker"
Série 21 "embout"
Series 21 "nipple"

641-643


PVDF-Sicherheitskupplung Raccord de sécurité PVDF PVDF safety coupling

CO K / KU / KA / KAU
COT / TA



15

Nr. No. No.	Bezeichnung Désignation Description	Material Matériau Material	Nr. No. No.	Bezeichnung Désignation Description	Material Matériau Material	Nr. No. No.	Bezeichnung Désignation Description	Material Matériau Material
1*	Schiebehülse blau Manchon couissant bleu Sliding sleeve blue	PVDF (FDA)	4	Druckfeder Ressort de compression Compression spring	Inox 1.4310	7	Ventileinsatz (Option) Emboîtement soupape (option) Valve insert (option)	PVDF (FDA)
2*	Dichtung Joint Seal	EPDM (FDA)	5	Rückstellfeder Ressort de rappel Return spring	PVDF (FDA)	8	Entriegelungssicherung Sécurité anti-déverrouillage Safety lock	PVDF (FDA)
3*	Farbmarkierung blau Repérage de couleur bleu Color coding blue	PVDF (FDA)	6	Spannzange Élément de connex. principal Collet	PVDF (FDA)			

Spezifikationen

Betriebsdruck (PN): 10 bar
Temperatur: -20°C bis +100°C
Sterilisierbar: bis +121°C
Sicherheitsfaktor: 1.5-fach

Merkmale

Speziell geeignet für anspruchsvolle Anwendungen u.a. in der chemischen und pharmazeutischen Industrie.

Im Medizinalbereich insbesondere geeignet zum Anschluss an Dialysator-Kartuschen.

* Optionen erhältlich

- 1 - Schiebehülse: rot, weiss
- 2 - Dichtung: FKM, Silikon
- 3 - Markierung: rot, weiss

Spécifications

Pression de service (PN): 10 bar
Température: -20°C à +100°C
Stérilisable: jusqu'à +121°C
Facteur de sécurité: 1.5 fois

Caractéristiques

Particulièrement indiqués pour des applications de pointe, dans l'industrie chimique et pharmaceutique par exemple.

Pour ce qui est du domaine médical, ils sont particulièrement indiqués pour le raccordement aux cartouches des dialyseurs.

* Options disponible

- 1 - Manchon: rouge, blanc
- 2 - Joint: FKM, silicone
- 3 - Repérage: rouge, blanc

Specifications

Working pressure (PN): 10 bar
Temperature: -20°C to +100°C
Sterilizable: up to +121°C
Safety factor: 1.5 times

Characteristics

Especially for demanding applications, for example in the chemical and pharmaceutical industries.

In medical technology ideal for connecting dialyser cartridges.


* Options available

- 1 - Sleeve: red, white
- 2 - Seal: FKM, silicone
- 3 - Coding: red, white

Druckverlustkurve Wasser

Courbe de perte de charge eau

Pressure loss curve for water



Kuppler

absperrend

nicht absperrend

Stecker

absperrend

nicht absperrend

Coupleur

obturant

non-obturant

Embout

obturant

non-obturant

Coupler

shut-off

no shut-off

Nipple


shut-off

no shut-off

Druckauswertungsgrad in % des PN

Coefficient de pression de service
admissible en % de PN

Pressure coefficient in % of PN



Bestellhinweis Materialbezeichnung

Codification pour commande

Order information material
description

Bsp.: Bestellnummer CO KA/BS-SOT-LW6-PE

Example: No de comm. CO KA/BS-SOT-LW6-PE

Example: Order no. CO KA/BS-SOT-LW6-PE

CO	CO	Kupplung	CO	Accouplement	CO	Coupling
KA/	K	Kuppler gerade nicht absperrend	K	Coupleur droit non-obturant	K	Coupler straight no shut-off
	KU	Kuppler abgewinkelt nicht absperrend	KU	Coupleur angulaire non-obturant	KU	Coupler angled no shut-off
	KA	Kuppler gerade absperrend	KA	Coupleur droit obturant	KA	Coupler straight shut-off
	KAU	Kuppler abgewinkelt absperrend	KAU	Coupleur angulaire obturant	KAU	Coupler angled shut-off
	T	Stecker gerade nicht absperrend	T	Embout droit non-obturant	T	Nipple straight no shut-off
	TA	Stecker gerade absperrend	TA	Embout droit obturant	TA	Nipple straight shut-off
BS-	BS	blau mit Sicherung	BS	bleu avec sécurité	BS	blue with safety lock
	NS	neutral (weiss) mit Sicherung *	NS	naturel (blanc) avec sécurité *	NS	nature (white) with safety lock *
	RS	rot mit Sicherung *	RS	rouge avec sécurité *	RS	red with safety lock *
	F	ohne Rückstellfeder, mit Sicherung *	F	sans ressort de rappel, avec sécurité *	F	without return spring, with safety lock *
SO	SO	SERTO	SO	SERTO	SO	SERTO
T-	T	Schlauchtülle	T	douille cannelée pour tuyau	T	hose nozzle
	I	Innengewinde	I	filetage femelle	I	female thread
	S	SERTO-Anschluss	S	raccordement SERTO	S	SERTO tube connector
LW6-	LW6	Anschlussgrösse für Schlauch id 6 mm	LW6	dimension du raccord p. tuyau id 6 mm	LW6	port size for hose id 6 mm
	1/4	Rohrgewinde zylindrisch	1/4	filetage BSP cylindrique	1/4	BSP thread straight
	6	für Rohrdurchmesser 6 mm	6	pour diamètre extérieur du tuyau 6 mm	6	for tube outside diameter 6 mm
P	PVDF		PVDF		PVDF	
E	Dichtung	E EPDM	Joint	E EPDM	Seal	E EPDM
		V FKM *		V FKM *		V FKM *
		S Silikon *		S Silicone *		S Silicone *

* Option auf Anfrage

* en option, sur demande

* optional, on request

Kuppler mit Innengewinde

nicht absperrend


Coupleur avec taraudage

non-obturant

Coupler with female thread

no shut-off

CO K/BS-SOI



Type -G	Mat.-Nr.	bar	SW	L	D	e	kg/100
G=Rohrgewinde (zylindrisch)			G=Filetage-gaz BSP (cylindrique)		G=BSP thread (parallel)		
CO K/BS-SOI-G $\frac{1}{4}$ PE	358.0114.001	10	19	51.0	40.0	8.4	3.400

Kuppler mit Innengewinde

absperrend


Coupleur avec taraudage

obturant

Coupler with female thread

shut-off

CO KA/BS-SOI



Type -G	Mat.-Nr.	bar	SW	L	D	e	kg/100
G=Rohrgewinde (zylindrisch)			G=Filetage-gaz BSP (cylindrique)		G=BSP thread (parallel)		
CO KA/BS-SOI-G $\frac{1}{4}$ PE	358.1114.001	10	19	51.0	40.0	8.4	3.500

Kuppler mit Schlauchtülle

nicht absperrend


Coupleur avec douille cannelée pour tuyau

non-obturant

Coupler with hose nozzle

no shut-off

CO K/BS-SOT



Type -LW	Mat.-Nr.	bar	SW	L	D1	D2	b	e	kg/100
CO K/BS-SOT-LW6 PE	358.0506.001	10	19	76.0	40.0	7.5	17.0	4.0	3.800
CO K/BS-SOT-LW8 PE	358.0508.001	10	19	76.0	40.0	9.5	17.0	6.0	3.800

Kuppler mit Schlauchtülle

absperrend


Coupleur avec douille cannelée pour tuyau

obturant

Coupler with hose nozzle

shut-off

CO KA/BS-SOT



Type -LW	Mat.-Nr.	bar	SW	L	D1	D2	b	e	kg/100
CO KA/BS-SOT-LW6 PE	358.1506.001	10	19	76.0	40.0	7.5	17.0	4.0	3.900
CO KA/BS-SOT-LW8 PE	358.1508.001	10	19	76.0	40.0	9.5	17.0	6.0	3.900

Kuppler mit SERTO-Anschluss

nicht absperrend


Coupleur avec connexion SERTO

non-obturant

Coupler with SERTO connection

no shut-off

CO K/BS-SOS



Type -d	Mat.-Nr.	bar	SW1	SW2	L	D	e	kg/100
CO K/BS-SOS-6 PE	358.0306.001	10	19	12	78.0	40.0	2.8	4.100
CO K/BS-SOS-8 PE	358.0308.001	10	19	14	79.0	40.0	4.8	4.200
CO K/BS-SOS-10 PE	358.0310.001	10	19	17	80.5	40.0	6.6	4.500

Kuppler mit SERTO-Anschluss

absperrend


Coupleur avec connexion SERTO

obturant

Coupler with SERTO connection

shut-off

CO KA/BS-SOS



Type -d	Mat.-Nr.	bar	SW1	SW2	L	D	e	kg/100
CO KA/BS-SOS-6 PE	358.1306.001	10	19	12	78.0	40.0	2.8	4.200
CO KA/BS-SOS-8 PE	358.1308.001	10	19	14	79.0	40.0	4.8	4.300
CO KA/BS-SOS-10 PE	358.1310.001	10	19	17	80.5	40.0	6.6	4.600

Kuppler mit Schlauchtülle abgewinkelt

nicht absperrend

Coupleur avec douille cannelée pour tuyau angulaire


non-obturant

Coupler with hose nozzle angled

no shut-off

CO KU/BS-SOT

Type -LW	Mat.-Nr.	bar	L	D1	D2	b	e	kg/100
CO KU/BS-SOT-LW8 PE	358.0408.001	10	51.0	40.0	9.5	17.0	6.0	3.300



Kuppler mit Schlauchtülle abgewinkelt

absperrend

Coupleur avec douille cannelée pour tuyau angulaire


obturant

Coupler with hose nozzle angled

shut-off

CO KAU/BS-SOT

Type -LW	Mat.-Nr.	bar	L	D1	D2	b	e	kg/100
CO KAU/BS-SOT-LW8 PE	358.1408.001	10	51.0	40.0	9.5	17.0	6.0	3.400



Kuppler mit SERTO-Anschluss abgewinkelt

nicht absperrend

Coupleur avec connexion SERTO angulaire


non-obturant

Coupler with SERTO connection angled

no shut-off

CO KU/BS-SOS

Type -d	Mat.-Nr.	bar	SW	L1	L2	D	e	kg/100
CO KU/BS-SOS-8 PE	358.0208.001	10	14	51.0	57.5	40.0	4.8	3.700
CO KU/BS-SOS-10 PE	358.0210.001	10	17	51.0	61.0	40.0	6.6	4.000



Kuppler mit SERTO-Anschluss abgewinkelt


absperrend

Coupleur avec connexion SERTO angulaire

obturant

Coupler with SERTO connection angled

shut-off



CO KAU/BS-SOS

Type -d	Mat.-Nr.	bar	SW	L1	L2	D	e	kg/100
CO KAU/BS-SOS-8 PE	358.1208.001	10	14	51.0	57.5	40.0	4.8	3.800
CO KAU/BS-SOS-10 PE	358.1210.001	10	17	51.0	61.0	40.0	6.6	4.100

Stecker mit Innengewinde


nicht absperrend

Embout avec taraudage

non-obturant

Nipple with female thread

no shut-off



CO T/B-SOI

Type -G	Mat.-Nr.	bar	SW	L1	L2	e	kg/100
G=Rohrgewinde (zylindrisch)	G=Filetage-gaz BSP (cylindrique)	G=BSP thread (parallel)					
CO T/B-SOI-G $\frac{1}{4}$ P	358.5114.000	10	19	41.5	19.5	8.4	1.000
CO T/B-SOI-G $\frac{3}{8}$ P	358.5138.000	10	22	41.5	19.5	8.4	1.100

Stecker mit Innengewinde


absperrend

Embout avec taraudage

obturant

Nipple with female thread

shut-off



CO TA/B-SOI

Type -G	Mat.-Nr.	bar	SW	L1	L2	e	kg/100
G=Rohrgewinde (zylindrisch)	G=Filetage-gaz BSP (cylindrique)	G=BSP thread (parallel)					
CO TA/B-SOI-G $\frac{1}{4}$ PE	358.6114.001	10	19	41.5	19.5	8.4	1.100
CO TA/B-SOI-G $\frac{3}{8}$ PE	358.6138.001	10	22	41.5	19.5	8.4	1.200

Stecker mit Schlauchtülle

nicht absperrend


Embout avec douille cannelée pour tuyau

non-obturant

Nipple with hose nozzle

no shut-off

CO T/B-SOT



Type -LW	Mat.-Nr.	bar	SW	L1	L2	D	b	e	kg/100
CO T/B-SOT-LW6 P	358.5506.000	10	19	66.5	44.5	7.5	17.0	4.0	1.500
CO T/B-SOT-LW8 P	358.5508.000	10	19	66.5	44.5	9.5	17.0	6.0	1.600
CO T/B-SOT-LW10 P	358.5510.000	10	22	67.5	45.5	11.5	19.0	7.0	1.900

Stecker mit Schlauchtülle

absperrend


Embout avec douille cannelée pour tuyau

obturant

Nipple with hose nozzle

shut-off

CO TA/B-SOT



Type -LW	Mat.-Nr.	bar	SW	L1	L2	D	b	e	kg/100
CO TA/B-SOT-LW6 PE	358.6506.001	10	19	66.5	44.5	7.5	17.0	4.0	1.600
CO TA/B-SOT-LW8 PE	358.6508.001	10	19	66.5	44.5	9.5	17.0	6.0	1.700
CO TA/B-SOT-LW10 PE	358.6510.001	10	22	67.5	45.5	11.5	19.0	7.0	2.000

Stecker mit SERTO-Anschluss

nicht absperrend


Embout avec connexion SERTO

non-obturant

Nipple with SERTO connection

no shut-off

CO T/B-SOS



Type -d	Mat.-Nr.	bar	SW1	SW2	L1	L2	e	kg/100
CO T/B-SOS-6 P	358.5306.000	10	19	12	68.0	46.0	2.8	1.700
CO T/B-SOS-8 P	358.5308.000	10	19	14	69.0	47.0	4.8	1.800
CO T/B-SOS-10 P	358.5310.000	10	22	17	70.5	48.5	6.6	2.100

Stecker mit SERTO-Anschluss

absperrend


Embout avec connexion

SERTO

obturant

Nipple with SERTO connection

shut-off




CO TA/B-SOS

Type -d	Mat.-Nr.	bar	SW1	SW2	L1	L2	e	kg/100
CO TA/B-SOS-6 PE	358.6306.001	10	19	12	68.0	46.0	2.8	1.800
CO TA/B-SOS-8 PE	358.6308.001	10	19	14	69.0	47.0	4.8	1.900
CO TA/B-SOS-10 PE	358.6310.001	10	22	17	70.5	48.5	6.6	2.200

PVDF Kupplung "Plus" Accouplement "Plus" PVDF PVDF coupling "Plus"

COP KA/NS
COP TA/NS



15

Nr. No. No.	Bezeichnung Désignation Description	Material Matériau Material	Nr. No. No.	Bezeichnung Désignation Description	Material Matériau Material	Nr. No. No.	Bezeichnung Désignation Description	Material Matériau Material
1	Kuppler Coupleur Coupler	PVDF (FDA)	4	Druckfeder Ressort de compression Compression spring	Hastelloy® 2.4610	7	Sicherungsklammer Clip de sécurité Safety clamp	PA
2	Stecker Embout Nipple	PVDF (FDA)	5*	Dichtung Joint Seal	EPDM (FDA)	8	Verliersicherung Fixation anti-perte Loss protection	EPDM
3	Ventilkegel Cône de soupape Valve cone	PVDF (FDA)	6	Verschlussmutter Ecrou de verrouillage Lock nut	PA/TPE			

Spezifikationen

Betriebsdruck (PN): 10 bar
Temperatur: -20°C bis +100°C
Sterilisierbar: bis +121°C
Sicherheitsfaktor: 1.5-fach

Merkmale

Schraubkupplung für höchste Sicherheit im Einsatz. Die Sicherungsklammer verhindert unbeabsichtigtes Lösen der Verschlussmutter. Optimale, tottraumarme Konstruktion für hohe Durchflussraten.

Optionen

- Varianten: mit Übergangsmuffe SO 20030

Spécifications

Pression de service (PN): 10 bar
Température: -20°C à +100°C
Stérilisable: jusqu'à +121°C
Facteur de sécurité: 1.5 fois

Caractéristiques

Accouplement par vis pour une sécurité maximale en utilisation. Le clip de sécurité empêche le détachement accidentelle d'ecrou de verrouillage. Construction optimisée avec un espace mort minimal pour des débits élevés.

Options

- Autres versions: avec adaptateur femelle SO 20030

Specifications

Working pressure (PN): 10 bar
Temperature: -20°C to +100°C
Sterilizable: up to +121°C
Safety factor: 1.5 times

Characteristics

Screw coupling for maximum safety in use. The safety clamp prevents accidental release of the lock nut. Optimised design with minimal dead space for high flow rates.


Options

- Other versions: with female adaptor SO 20030

Druckverlustkurve Wasser

Courbe de perte de charge eau

Pressure loss curve for water



Druckauswertungsgrad in % des PN

 Coefficient de pression de service
admissible en % de PN

Pressure coefficient in % of PN

°C												
-100°	-40°	-20°	0°	23°	40°	60°	80°	100°	150°	200°	250°	300°
			60 %	100 %	75 %	60 %	45 %	25 %				

Kuppler mit SERTO-Anschluss

absperrend


Coupleur avec connexion SERTO

obturant

Coupler with SERTO connection

shut-off

COP KA/NS-SOS



Type -d	Mat.-Nr.	bar	SW1	SW2	L	D	z	e	kg/100
COP KANS-SOS-129 E	348.6212.031	10	19	19	80.0	35.0	50.5	7.0	5.500

Stecker mit SERTO-Anschluss

absperrend


Embout avec connexion SERTO

obturant

Nipple with SERTO connection

shut-off

COP TA/NS-SOS



Type -d	Mat.-Nr.	bar	SW1	SW2	L	D	H	z	e	kg/100
COP TANS-SOS-129 E	348.3212.031	10	19	19	85.0	40.0	54.0	50.5	7.0	6.000

Kupplungen PVDF Serie 21

Coupleurs PVDF série 21

Couplings PVDF series 21

Materialien Serie 21

- Kuppler und Stecker: PVDF weiss
- Federn: Edelstahl 1.4571
- Dichtung: FKM

Nennweite

5 = 20 mm²


Betriebstemperatur

-20°C bis +120°C
sterilisierbar bis +160°C
(abhängig vom Durchflussmedium)


Betriebsdruck

8 bar bei +23°C
maximaler statischer Betriebsdruck (ohne Pulsation) bei min. 4-facher statischer Sicherheit

Kupplungsfunktionen



beidseitig absperrend
Kuppler absperrend <CO KA...>
Stecker absperrend <CO TA...>



einseitig absperrend
Kuppler absperrend <CO KA...>
Stecker nicht absperrend <CO T...>


Eigenschaften

- überdurchschnittliche Durchflussleistung
- Einhandbedienung

Merkmale

- Funktion: Mini-Industriekupplung
- Einsatz: Medizintechnik, Lebensmittel, Laborbereich
- Medien: Flüssigkeiten, Gase, Vakuum 87 %

Durchflussleistung



Matériaux séries 21

- Coupleur et embout: PVDF blanc
- Ressorts: acier inoxydable 1.4571
- Joint torique: FKM

Largeur nominale

5 = 20 mm²


Plage de température

-20°C jusqu'à +120°C
stérilisable jusqu'à +160°C
(en fonction du fluide d'écoulement)


Pression de service

8 bar à +23°C
pression de service statique max. (sans pulsation) avec un facteur de sécurité statique min. de 4

Fonctions d'accouplement



obturant dans les deux sens
coupleur obturant <CO KA...>
embout obturant <CO TA...>



obturant dans un sens
coupleur obturant <CO KA...>
embout non-obturant <CO T...>


Propriétés

- capacité d'écoulement supérieure à la moyenne
- utilisation à une seule main

Caractéristiques

- Fonction: mini-raccord industriel
- Application: technologie médicale, industrie alimentaire, laboratoires
- Médium: fluides, gaz, vide 87 %

Débit



Materials series 21

- Coupler and nipple: PVDF white
- Spring: stainless steel 1.4571
- Seals: FKM

Nominal bore

5 = 20 mm²


Temperature range

-20°C up to +120°C
sterilizable up to +160°C
(depending on medium used)


Working pressure

8 bar at +23°C
maximum static operating pressure (without pulsation) at min. static safety of 4

Coupling functions



double-sided shut-off
coupler shut-off <CO KA...>
nipple shut-off <CO TA...>



one-sided shut-off
coupler shut-off <CO KA...>
nipple no shut-off <CO T...>

Properties

- above-average flow rate
- one-handed operation

Characteristics

- Function: mini industrial coupling
- Uses: medical technology, food industry, laboratories
- Media: fluids, gases, vacuum 87 %

Flow capacity



Kuppler mit Schlauchtülle

absperrend


Coupleur avec douille cannelée

obturant

Coupler with hose nozzle

shut-off

CO KA 211 (P)



Type -LW	Mat.-Nr.	bar	SW	L	b	D	kg/100
CO KA 211-LW 4 P	302.8110.040	8	17	60.0	17.0	25.5	1.510
CO KA 211-LW 6 P	302.8110.060	8	17	60.0	17.0	25.5	1.580

Kuppler mit Innengewinde

absperrend


Coupleur avec taraudage

obturant

Coupler with female thread

shut-off

CO KA 212 (P)



Type -G	Mat.-Nr.	bar	SW	L1	L2	D	kg/100
G=Rohrgewinde (zylindrisch)	G=Filetage-gaz BSP (cylindrique)					G=BSP thread (parallel)	
CO KA 212-G 1/8 P	302.8120.020	8	17	53.0	8.0	25.5	1.300
CO KA 212-G 1/4 P	302.8120.040	8	17	39.0	9.0	25.5	1.030

Kuppler mit Aussengewinde

absperrend


Coupleur avec filetage

obturant

Coupler with male thread

shut-off

CO KA 213 (P)



Type -G	Mat.-Nr.	bar	SW	L	i	D	kg/100
G=Rohrgewinde (zylindrisch)	G=Filetage-gaz BSP (cylindrique)					G=BSP thread (parallel)	
CO KA 213-G 1/8 P	302.8130.020	8	17	50.0	7.0	25.5	1.530
CO KA 213-G 1/4 P	302.8130.040	8	17	52.0	7.0	25.5	1.570

Kuppler mit Rohranschluss

absperrend


Coupleur avec connexion pour tube

obturant

Coupler with tube connection

shut-off

CO KA 214 (P)



Type -d	Mat.-Nr.	bar	SW	L1	L2	D	kg/100
CO KA 214-6 P	302.8140.060	8	17	68.0	18.0	25.5	1.820
CO KA 214-8 P	302.8140.080	8	17	68.0	18.0	25.5	1.930

Kuppler in Schottausführung mit Rohranschluss

absperrend


Coupleur traversée de cloison avec connexion pour tube

obturant

Panel mount coupler with tube connection

shut-off

CO KA 215 (P)



Type -d	Mat.-Nr.	bar	M	SW1	SW2	L1	L2	D	kg/100
CO KA 215-6 P	302.8740.060	8	25x1.0	17	27	56.0	13.0	28.0	2.840
CO KA 215-8 P	302.8740.080	8	25x1.0	17	27	56.0	13.0	28.0	2.890

Kuppler in Schottausführung mit Schlauchtülle

absperrend


Coupleur traversée de cloison avec douille cannelée

obturant

Coupler panel mount with hose nozzle

shut-off

CO KA 216 (P)



Type -LW	Mat.-Nr.	bar	M	SW1	SW2	L	D	b	kg/100
CO KA 216-LW 4 P	302.8710.040	8	25x1.0	17	27	60.0	28.0	17.0	2.700
CO KA 216-LW 6 P	302.8710.060	8	25x1.0	17	27	60.0	28.0	17.0	2.770

Stecker mit Schlauchtülle

nicht absperrend


Embout avec douille cannelée pour tuyau

non-obturant

Nipple with hose nozzle

no shut-off

COT 211 (P)



Type -LW	Mat.-Nr.	bar	L	b	kg/100
COT 211-LW 4 P	302.6010.040	8	32.0	17.0	0.100
COT 211-LW 6 P	302.6010.060	8	32.0	17.0	0.110

Stecker mit Schlauchtülle

absperrend


Embout avec douille cannelée pour tuyau

obturant

Nipple with hose nozzle

shut-off

CO TA 211 (P)



Type -LW	Mat.-Nr.	bar	SW	L	b	kg/100
CO TA 211-LW 4 P	302.6110.040	8	17	46.0	17.0	0.630
CO TA 211-LW 6 P	302.6110.060	8	17	46.0	17.0	0.660

Stecker mit Innengewinde

nicht absperrend


Embout avec taraudage

non-obturant

Nipple with female thread

no shut-off

COT 212 (P)



Type -G	Mat.-Nr.	bar	SW	L1	L2	kg/100
G=Rohrgewinde (zylindrisch)	G=Filetage-gaz BSP (cylindrique)		G=BSP thread (parallel)			
COT 212-G $\frac{1}{8}$ P	302.6020.020	8	14	24.0	8.0	0.190
COT 212-G $\frac{1}{4}$ P	302.6020.040	8	17	25.0	9.0	0.330

Stecker mit Innengewinde


absperrend

Embout avec taraudage

obturant

Nipple with female thread

shut-off



CO TA 212 (P)

Type -G	Mat.-Nr.	bar	SW	L1	L2	kg/100
G=Rohrgewinde (zylindrisch)	G=Filetage-gaz BSP (cylindrique)		G=BSP thread (parallel)			
CO TA 212-G $\frac{1}{8}$ P	302.6120.020	8	17	39.0	8.0	0.840
CO TA 212-G $\frac{1}{4}$ P	302.6120.040	8	17	42.0	10.0	1.150

Stecker mit Aussengewinde


nicht absperrend

Embout avec filetage

non-obturant

Nipple with male thread

no shut-off



CO T 213 (P)

Type -G	Mat.-Nr.	bar	SW	L	i	kg/100
G=Rohrgewinde (zylindrisch)	G=Filetage-gaz BSP (cylindrique)		G=BSP thread (parallel)			
CO T 213-G $\frac{1}{8}$ P	302.6030.020	8	14	25.0	7.0	0.220
CO T 213-G $\frac{1}{4}$ P	302.6030.040	8	17	28.0	9.0	0.340

Stecker mit Aussengewinde


absperrend

Embout avec filetage

obturant

Nipple with male thread

shut-off



CO TA 213 (P)

Type -G	Mat.-Nr.	bar	SW	L	i	kg/100
G=Rohrgewinde (zylindrisch)	G=Filetage-gaz BSP (cylindrique)		G=BSP thread (parallel)			
CO TA 213-G $\frac{1}{8}$ P	302.6130.020	8	17	36.0	7.0	0.750
CO TA 213-G $\frac{1}{4}$ P	302.6130.040	8	17	38.0	7.0	0.790

Stecker mit Rohranschluss


nicht absperrend

Embout avec connexion pour tube

non-obturant

Nipple with tube connection

no shut-off



COT 214 (P)

Type -d	Mat.-Nr.	bar	SW	L1	L2	kg/100
COT 214-6 P	302.6040.060	8	14	32.0	13.0	0.340
COT 214-8 P	302.6040.080	8	14	32.0	13.0	0.420

Kupplungen POM Serie K-CP Coupleurs POM série K-CP Couplings POM series K-CP

Materialien

- Kuppler und Stecker: POM
- Dichtungen: NBR
- Clip: Edelstahl 1.4401

Nennweite (NW)

K-CP..2-... = 3.2 mm
K-CP..4-... = 6.4 mm


Betriebstemperatur

-40°C bis +80°C


Betriebsdruck

8 bar bei +23°C


Kupplungsfunktionen



beidseitig absperrend
Kuppler absperrend KV-CP...
Stecker absperrend KSV-CP...



einseitig absperrend
Kuppler absperrend KV-CP...
Stecker nicht absperrend KS-CP...



nicht absperrend
Kuppler nicht absperrend K-CP...
Stecker nicht absperrend KS-CP...

Eigenschaften


- Einhandbedienung
- hoher Durchfluss
- kleine Baugrößen
- hohe chemische Beständigkeit

Merkmale

- Einsatz: Instrumentenausrüstungen, Kühlrohrleitungen
- Medien: Luft, Säuren

Durchflussleistung K-CP..2-...

(Bsp. K-CPB2-1/8 K)



Matériaux

- Coupleur et embout: POM
- Joints: NBR
- Clip: acier inoxydable 1.4401

Largeur nominale (NW)

K-CP..2-... = 3.2 mm
K-CP..4-... = 6.4 mm


Plage de température

-40°C jusqu'à +80°C


Pression de service

8 bar à +23°C


Fonctions d'accouplement



obturant dans les deux sens
coupleur obturant KV-CP...
embout obturant KSV-CP...



obturant dans un sens
coupleur obturant KV-CP...
embout non-obturant KS-CP...



non-obturant
coupleur non-obturant K-CP...
embout non-obturant KS-CP...

Propriétés


- utilisation à une seule main
- un grand écoulement
- de petites dimensions
- haute résistance chimique

Caractéristiques

- Application: équipements d'instruments, conduites de refroidissement
- Médium: air, acides

Débit K-CP..2-...

(par ex. K-CPB2-1/8 K)



Materials

- Coupler and nipple: POM
- Seals: NBR
- Clip: stainless steel 1.4401

Nominal bore (NW)

K-CP..2-... = 3.2 mm
K-CP..4-... = 6.4 mm


Temperature range

-40°C up to +80°C


Working pressure

8 bar at +23°C


Coupling functions



double-sided shut-off
coupler shut-off KV-CP...
nipple shut-off KSV-CP...



one-sided shut-off
coupler shut-off KV-CP...
nipple no shut-off KS-CP...



no shut-off
coupler no shut-off K-CP...
nipple no shut-off KS-CP...

Properties

- one-handed operation
- high flow rate
- compact dimensions
- high chemical resistance

Characteristics

- Uses: instrumentation, cooling tubes
- Media: air, acids


Flow capacity K-CP..2-...

(for ex. K-CPB2-1/8 K)

Durchflussleistung K-CP..4-...

(Bsp. K-CPB4-1/4 K)


Medium: Luft / Air / Air
(100 psig inlet pressure)



Débit K-CP..4-...

(Bsp. K-CPB4-1/4 K)

Medium: Wasser / Eau / Water



Flow capacity K-CP..4-...

(Bsp. K-CPB4-1/4 K)



Kuppler mit Aussengewinde

nicht absperrend


Coupleur avec filetage

non-obturant

Coupler with male thread

no shut-off

K-CPB



Type -R	Mat.-Nr.	bar	NW	SW	L	i	kg/100
R=Rohrgewinde (kegelig)	R=Filetage-gaz BSP (conique)						
K-CPB2-1/8	YBD.CPB2.113020	8	3.2	15	25.4	10.2	0.490
K-CPB4-1/4	YBD.CPB4.113040	8	6.4	18	29.4	12.7	0.680

Kuppler mit Aussengewinde

absperrend


Coupleur avec filetage

obturant

Coupler with male thread

shut-off

KV-CPB



Type -R	Mat.-Nr.	bar	NW	SW	L	i	kg/100
R=Rohrgewinde (kegelig)	R=Filetage-gaz BSP (conique)						
KV-CPB2-1/8	YBD.CPB2.123020	8	3.2	15	25.4	10.2	0.550
KV-CPB4-1/4	YBD.CPB4.123040	8	6.4	15	29.4	12.7	0.740
KV-CPB4-3/8	YBD.CPB4.123060	8	6.4	18	29.4	12.7	0.760

Kuppler mit Schlauchtülle

nicht absperrend


Coupleur avec douille cannelée pour tuyau

non-obturant

Coupler with hose nozzle

no shut-off

K-CPC



Type -LW	Mat.-Nr.	bar	NW	L	D1	D2	b	kg/100
K-CPC2-LW 4	YBD.CPC2.117040	8	3.2	42.0	20.0	5.0	11.4	0.550
K-CPC2-LW 5	YBD.CPC2.117050	8	3.2	47.2	20.0	6.0	16.5	0.560
K-CPC2-LW 6,5	YBD.CPC2.117060	8	3.2	47.2	20.0	7.5	16.5	0.580
K-CPC4-LW 6,5	YBD.CPC4.117060	8	6.4	49.5	23.4	7.5	16.5	0.620
K-CPC4-LW 8	YBD.CPC4.117080	8	6.4	49.5	23.4	9.0	16.5	0.720
K-CPC4-LW 9,5	YBD.CPC4.117090	8	6.4	49.5	23.4	10.5	16.5	0.760

Kuppler mit Schlauchtülle


absperrend

Coupleur avec douille cannelée pour tuyau

obturant

Coupler with hose nozzle

shut-off



KV-CPC

Type -LW	Mat.-Nr.	bar	NW	L	D1	D2	b	kg/100
KV-CPC2-LW 4	YBD.CPC2.127040	8	3.2	42.0	20.0	5.0	11.4	0.740
KV-CPC2-LW 5	YBD.CPC2.127050	8	3.2	47.2	20.0	6.0	16.5	0.760
KV-CPC2-LW 6,5	YBD.CPC2.127060	8	3.2	47.2	20.0	7.5	16.5	0.650
KV-CPC4-LW 6,5	YBD.CPC4.127060	8	6.4	49.5	23.4	7.5	16.5	0.920
KV-CPC4-LW 8	YBD.CPC4.127080	8	6.4	49.5	23.4	9.0	16.5	0.850
KV-CPC4-LW 9,5	YBD.CPC4.127090	8	6.4	49.5	23.4	10.5	16.5	0.940

Kuppler in Schottausführung mit Schlauchtülle


nicht absperrend

Coupleur traversée de cloison avec douille cannelée pour tuyau

non-obturant

Panel mount coupler with hose nozzle

no shut-off



K-CPH

Type -LW	Mat.-Nr.	bar	NW	SW	L	D	B	b	kg/100
K-CPH2-LW 4	YBD.CPH2.118040	8	3.2	15	41.9	5.0	13.0	11.4	0.750
K-CPH2-LW 5	YBD.CPH2.118050	8	3.2	15	47.0	6.0	13.0	16.5	0.830
K-CPH2-LW 6,5	YBD.CPH2.118060	8	3.2	15	47.0	7.5	13.0	16.5	0.860
K-CPH4-LW 6,5	YBD.CPH4.118060	8	6.4	20	49.5	7.5	17.5	16.5	1.320
K-CPH4-LW 8	YBD.CPH4.118080	8	6.4	20	49.5	9.0	17.5	16.5	1.360
K-CPH4-LW 9,5	YBD.CPH4.118090	8	6.4	20	49.5	10.5	17.5	16.5	1.380

Kuppler in Schottausführung mit Schlauchtülle

absperrend


Coupleur traversée de cloison avec douille cannelée pour tuyau

obturant

Panel mount coupler with hose nozzle

shut-off

KV-CPH



Type -LW	Mat.-Nr.	bar	NW	SW	L	D	B	b	kg/100
KV-CPH2-LW 4	YBD.CPH2.128040	8	3.2	15	41.9	5.0	13.0	11.4	0.820
KV-CPH2-LW 5	YBD.CPH2.128050	8	3.2	15	47.0	6.0	13.0	16.5	0.860
KV-CPH2-LW 6,5	YBD.CPH2.128060	8	3.2	15	47.0	7.5	13.0	16.5	0.890
KV-CPH4-LW 6,5	YBD.CPH4.128060	8	6.4	20	49.5	7.5	17.0	16.5	1.380
KV-CPH4-LW 8	YBD.CPH4.128080	8	6.4	20	49.5	9.0	17.0	16.5	1.420
KV-CPH4-LW 9,5	YBD.CPH4.128090	8	6.4	20	49.5	10.5	17.0	16.5	1.440

Stecker mit Aussengewinde

nicht absperrend


Embout avec filetage

non-obturant

Nipple with male thread

no shut-off

KS-CPB



Type -R	Mat.-Nr.	bar	NW	SW	L	i	kg/100
R=Rohrgewinde (kegelig)	R=Filetage-gaz BSP (conique)					R=BSP thread (tapered)	
KS-CPB2-1/8	YBD.CPB2.133020	8	3.2	12	14.7	10.2	0.180
KS-CPB4-1/4	YBD.CPB4.133040	8	6.4	15	17.6	12.7	0.340
KS-CPB4-3/8	YBD.CPB4.133060	8	6.4	18	17.8	12.7	0.600

Stecker mit Aussengewinde

absperrend


Embout avec filetage

obturant

Nipple with male thread

shut-off

KSV-CPB



Type -R	Mat.-Nr.	bar	NW	SW	L	i	kg/100
R=Rohrgewinde (kegelig)	R=Filetage-gaz BSP (conique)					R=BSP thread (tapered)	
KSV-CPB2-1/8	YBD.CPB2.143020	8	3.2	12	22.4	10.2	0.330
KSV-CPB4-1/4	YBD.CPB4.143040	8	6.4	15	25.0	12.7	0.420
KSV-CPB4-3/8	YBD.CPB4.143060	8	6.4	18	19.0	12.7	0.680

Stecker mit Schlauchtülle


nicht absperrend

Embout avec douille cannelée pour tuyau

non-obturant

Nipple with hose nozzle

no shut-off



KS-CPC

Type -LW	Mat.-Nr.	bar	NW	L	D1	D2	b	kg/100
KS-CPC2-LW 4	YBD.CPC2.137040	8	3.2	15.2	12.7	5.0	11.4	0.130
KS-CPC2-LW 5	YBD.CPC2.137050	8	3.2	20.3	12.7	6.0	16.5	0.160
KS-CPC2-LW 6,5	YBD.CPC2.137060	8	3.2	20.3	12.7	7.5	16.5	0.150
KS-CPC4-LW 6,5	YBD.CPC4.137060	8	6.4	20.3	15.9	7.5	16.5	0.150
KS-CPC4-LW 8	YBD.CPC4.137080	8	6.4	20.3	15.9	9.0	16.5	0.250
KS-CPC4-LW 9,5	YBD.CPC4.137090	8	6.4	20.3	15.9	10.0	16.5	0.300

Stecker mit Schlauchtülle


absperrend

Embout avec douille cannelée pour tuyau

obturant

Nipple with hose nozzle

shut-off



KSV-CPC

Type -LW	Mat.-Nr.	bar	NW	L	D1	D2	b	kg/100
KSV-CPC2-LW 4	YBD.CPC2.147040	8	3.2	27.8	12.7	5.0	11.4	0.300
KSV-CPC2-LW 5	YBD.CPC2.147050	8	3.2	33.3	12.7	6.0	16.5	0.150
KSV-CPC2-LW 6,5	YBD.CPC2.147060	8	3.2	28.7	12.7	7.5	16.5	0.320
KSV-CPC4-LW 6,5	YBD.CPC4.147060	8	6.4	33.2	15.9	7.5	16.5	0.540
KSV-CPC4-LW 8	YBD.CPC4.147080	8	6.4	33.2	15.9	9.0	16.5	0.530
KSV-CPC4-LW 9,5	YBD.CPC4.147090	8	6.4	34.0	15.9	10.5	16.5	0.510

Stecker mit Schlauchtülle 90°


nicht absperrend

Embout avec douille cannelée pour tuyau 90°

non-obturant

Nipple with hose nozzle 90°

no shut-off



KS-CPQ

Type -LW	Mat.-Nr.	bar	NW	L1	L2	D	b	kg/100
KS-CPQ2-LW 4	YBD.CPQ2.137040	8	3.2	25.1	10.2	5.0	11.4	0.130
KS-CPQ2-LW 6,5	YBD.CPQ2.137060	8	3.2	30.3	14.0	7.5	16.5	0.210
KS-CPQ4-LW 6,5	YBD.CPQ4.137060	8	6.4	33.5	13.8	7.5	16.5	0.250
KS-CPQ4-LW 9,5	YBD.CPQ4.137090	8	6.4	32.5	18.2	10.5	16.5	0.340

Stecker mit Schlauchtülle 90°


absperrend

Embout avec douille cannelée pour tuyau 90°

obturant

Nipple with hose nozzle 90°

shut-off



KSV-CPQ

Type -LW	Mat.-Nr.	bar	NW	L1	L2	D	b	kg/100
KSV-CPQ2-LW 4	YBD.CPQ2.148040	8	3.2	24.0	16.1	5.0	11.4	0.300
KSV-CPQ2-LW 6,5	YBD.CPQ2.148060	8	3.2	29.2	15.9	7.5	16.5	0.330
KSV-CPQ4-LW 6,5	YBD.CPQ4.148060	8	6.4	32.3	17.0	7.5	16.5	0.500
KSV-CPQ4-LW 9,5	YBD.CPQ4.148090	8	6.4	32.5	18.2	10.5	16.5	0.730